

# **Wyatt Instrument Firmware Update Guide**

#### **Summary**

This Technical Note describes how to install a firmware update on a Wyatt instrument. It is written using a *DynaPro NanoStar* instrument and *NanoStar Firmware Version 2.3.4.6* as an example. However, the process for updating firmware on any other instrument is essentially identical to this one, so this method can be applied to any instrument.



TN2501 Firmware Updater Connection Troubleshooting

Instrument User's Guides




#### **Contents**

Checking Your Firmware Version and Serial Num	ber 2
Updating from a Firmware CD	2
Updating from Wyatt.com	2
Running the Installer	4

#### **Checking Your Firmware Version and Serial Number**

Before running the Firmware Installer, check the current Firmware version on the system tab of your instrument's front panel. You might actually be up to date! This is also a good time to confirm the serial number of your instrument.




## **Updating from a Firmware CD**


If you prefer to perform the firmware update from a CD instead of downloading the installer from our website, please contact us at <a href="mailto:support@wyatt.com">support@wyatt.com</a> and we will be glad to mail you a firmware CD.

# **Updating from Wyatt.com**

To download the firmware update from our website, go to <a href="http://www.wyatt.com/firmware">http://www.wyatt.com/firmware</a> and choose the instrument that you would like to update.



On the next page, click the link to download the firmware update.




A zip file containing the installer will download. You should be able to run the installer (.exe) from the zip file. If you are unable, try copying the installer to your desktop and running it from there. Also, please note that you will need to run this file from a computer that communicates with your Wyatt instrument (generally the lab computer that controls your instrument).


### **Running the Installer**

From this point forward, it no longer matters whether the installer came from a CD or the website. The procedure is the same either way.


Double-click on the executable, which will be named *DPN-2.3.4.6-Customer.exe* or *DPN-2.3.4.6-Installer.exe*, to launch the Updater. Close all Windows programs and click next to continue the update.




Check the box that says you have read the Package Information above, then click Next. (If you do not check the circled box, you will not be able to click Next.)



The next page is a Windows Firewall Alert. When you click next on the Firewall Alert page, the updater will search for instruments that it can connect to.




The Updater will list all instruments that it can find on the network. Highlight the instrument you wish to update, as shown below, or manually enter the instrument's IP address on the bottom right of the screen. Then click the Install button on the updater.




Note: If you have multiple instruments of the same type on your network, you can check that you have selected the correct one by making sure the serial number of the instrument you've selected matches the serial number on the system tab of your instrument (see "Checking Your Firmware Version and Serial Number"). It is also a good idea to make note of the IP Address of your instrument as it appears in the Updater Window.

When the update has finished running on the computer, the following window will show up. You are now done with loading the new firmware onto your instrument. Click "Finish".




For firmware released in October 2013 or later, the Firmware Updater will automatically restart the instrument to complete the firmware update process.

**Important note:** If the instrument does not restart on its own, the user must perform a manual reboot. To do so, go to the instrument and select the "Restart Instrument" button on the bottom right of the system tab.




When you hit the Restart Instrument button, a dialogue box will appear. Confirm the restart by selecting "Yes".




When performing a firmware update, do NOT use the on/off switch on the front of the instrument to restart it!



While your instrument reboots, the firmware update installer will run on your instrument.



After the installer has run on your instrument, go to the System tab to confirm that the newest firmware version has been installed.



Please contact Wyatt Technology at <a href="mailto:support@wyatt.com">support@wyatt.com</a> (in North America) or your local distributor listed at <a href="https://www.wyatt.com/Distributors">www.wyatt.com/Distributors</a> if you have any questions about this procedure or if you like any assistance with your firmware update.

© Wyatt Technology Corporation 2015 - All Rights Reserved

